

Material Safety Data Sheet

1. MATERIAL AND COMPANY IDENTIFICATION

**Material Name** : AEROSHELL Turbine Oil 500  
**Uses** : Synthetic lubricating oil for aircraft turbine engines. For further details consult the AeroShell Book on www.shell.com/aviation.

**Manufacturer/Supplier** : SOPUS Products  
PO BOX 4427  
Houston, TX 77210-4427  
USA

**MSDS Request** : 877-276-7285

**Emergency Telephone Number**  
**Spill Information** : 877-242-7400  
**Health Information** : 877-504-9351

2. COMPOSITION/INFORMATION ON INGREDIENTS

Blend of synthetic esters and additives.

3. HAZARDS IDENTIFICATION

Emergency Overview	
<b>Appearance and Odour</b>	: Yellow to brown. Liquid. Slight hydrocarbon.
<b>Health Hazards</b>	: May cause sensitisation by skin contact.
<b>Safety Hazards</b>	: Not classified as flammable but will burn.
<b>Environmental Hazards</b>	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Health Hazards**

**Inhalation** : Under normal conditions of use, this is not expected to be a primary route of exposure.

**Skin Contact** : May cause sensitisation by skin contact. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

**Eye Contact** : May cause slight irritation to eyes.

**Ingestion** : Low toxicity if swallowed.

**Other Information** : May contain mixed isomers of tricresyl phosphate. Tricresyl phosphate may be absorbed either through the skin, by ingestion or by inhalation. These effects are delayed and may be permanent depending upon the degree of exposure. However, the concentration of these harmful isomers of TCP in this product is so low that neurotoxic effects are not expected. Used oil may contain harmful impurities.

**Signs and Symptoms** : Skin sensitisation (allergic skin reaction) signs and symptoms may include itching and/or a rash. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots

Material Safety Data Sheet

on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

**Aggravated Medical Condition** : Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material: Skin.

**Environmental Hazards** : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Additional Information** : Under normal conditions of use or in a foreseeable emergency, this product meets the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

4. FIRST AID MEASURES

**Inhalation** : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

**Skin Contact** : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

**Eye Contact** : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

**Ingestion** : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

**Advice to Physician** : Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

**Flash point** : Typical 260 °C / 500 °F (COC)

**Upper / lower Flammability or Explosion limits** : Typical 1 - 10 %(V)

**Auto ignition temperature** : > 320 °C / 608 °F

**Specific Hazards** : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

**Suitable Extinguishing Media** : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

**Unsuitable Extinguishing Media** : Do not use water in a jet.

**Protective Equipment for Firefighters** : Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

**Protective measures** : Avoid contact with skin and eyes. Use appropriate containment

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

- Clean Up Methods** : to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
- Additional Advice** : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
- Local authorities should be advised if significant spillages cannot be contained.

7. HANDLING AND STORAGE

- General Precautions** : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Handling** : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
- Storage** : Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: -50 - 50 °C / -58 - 122 °F
- Recommended Materials** : For containers or container linings, use mild steel or high density polyethylene.
- Unsuitable Materials** : PVC.
- Additional Information** : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Contains no components with occupational exposure limit values

- Exposure Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- Personal Protective Equipment** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

- Respiratory Protection** : No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)].
- Hand Protection** : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- Eye Protection** : Wear safety glasses or full face shield if splashes are likely to occur.
- Protective Clothing** : Skin protection not ordinarily required beyond standard issue work clothes.
- Monitoring Methods** : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
- Environmental Exposure Controls** : Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Yellow to brown. Liquid.
- Odour** : Slight hydrocarbon.
- pH** : Not applicable.
- Initial Boiling Point and Boiling Range** : > 280 °C / 536 °F estimated value(s)
- Pour point** : < -57 °C / -71 °F
- Flash point** : Typical 260 °C / 500 °F (COC)
- Upper / lower Flammability or Explosion limits** : Typical 1 - 10 %(V)
- Auto-ignition temperature** : > 320 °C / 608 °F
- Vapour pressure** : < 0.5 Pa at 20 °C / 68 °F (estimated value(s))
- Density** : Typical 1,005 kg/m3 at 15 °C / 59 °F
- Water solubility** : Negligible.

## Material Safety Data Sheet

n-octanol/water partition coefficient (log Pow) : > 6 (based on information on similar products)  
Kinematic viscosity : Typical 27 mm<sup>2</sup>/s at 40 °C / 104 °F  
Vapour density (air=1) : > 1 (estimated value(s))  
Evaporation rate (nBuAc=1) : Data not available

### 10. STABILITY AND REACTIVITY

**Stability** : Stable.  
**Conditions to Avoid** : Extremes of temperature and direct sunlight.  
**Materials to Avoid** : Strong oxidising agents.  
**Hazardous Decomposition Products** : Hazardous decomposition products are not expected to form during normal storage.

### 11. TOXICOLOGICAL INFORMATION

**Basis for Assessment** : Information given is based on data on the components and the toxicology of similar products.  
**Acute Oral Toxicity** : Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat  
**Acute Dermal Toxicity** : Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit  
**Acute Inhalation Toxicity** : Not considered to be an inhalation hazard under normal conditions of use.  
**Skin Irritation** : Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.  
**Eye Irritation** : Expected to be slightly irritating.  
**Respiratory Irritation** : Inhalation of vapours or mists may cause irritation.  
**Sensitisation** : Expected to be a skin sensitizer.  
**Repeated Dose Toxicity** : Not expected to be a hazard.  
**Mutagenicity** : Not considered a mutagenic hazard.  
**Carcinogenicity** : Components are not known to be associated with carcinogenic effects.  
**Reproductive and Developmental Toxicity** : Not expected to be a hazard.  
**Additional Information** : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

### 12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

**Acute Toxicity** : Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract).  
**Mobility** : Liquid under most environmental conditions. Floats on water. If

## Material Safety Data Sheet

it enters soil, it will adsorb to soil particles and will not be mobile.  
**Persistence/degradability** : Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.  
**Bioaccumulation** : Contains components with the potential to bioaccumulate.  
**Other Adverse Effects** : Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

### 13. DISPOSAL CONSIDERATIONS

**Material Disposal** : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.  
**Container Disposal** : Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
**Local Legislation** : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

### 14. TRANSPORT INFORMATION

**US Department of Transportation Classification (49CFR)**  
This material is not subject to DOT regulations under 49 CFR Parts 171-180.

**IMDG**  
This material is not classified as dangerous under IMDG regulations.

**IATA (Country variations may apply)**  
This material is not classified as dangerous under IATA regulations.

### 15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### Federal Regulatory Status

#### Notification Status

EINECS	All components listed.
TSCA	All components listed.
DSL	All components listed.

**AEROSHELL Turbine Oil 500**

MSDS# 857490E

Version 5.0

Effective Date 07/03/2008

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

**Material Safety Data Sheet**

**SARA Hazard Categories (311/312)**

Immediate (Acute) Health Hazard.

**State Regulatory Status**

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)**

This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

**New Jersey Right-To-Know Chemical List**

Tricresyl phosphate (1330-78-5)

Listed.

---

**16. OTHER INFORMATION**

**NFPA Rating (Health, Fire, Reactivity)** : 0, 1, 0

**MSDS Version Number** : 5.0

**MSDS Effective Date** : 07/03/2008

**MSDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from the previous version.

**MSDS Regulation** : The content and format of this MSDS is in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Uses and Restrictions** : This product must be used, handled and applied in accordance with the requirements of the equipment manufacturer's manuals, bulletins and other documentation.

**MSDS Distribution** : The information in this document should be made available to all who may handle the product.

**Disclaimer** : The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.